

549,383

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau(43) International Publication Date
30 September 2004 (30.09.2004)

PCT

(10) International Publication Number
WO 2004/084367 A1(51) International Patent Classification⁷: H01T 13/20,
13/39 // B23K 20/08(21) International Application Number:
PCT/FI2004/050025

(22) International Filing Date: 10 March 2004 (10.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20030401 18 March 2003 (18.03.2003) FI(71) Applicant (for all designated States except US): WÄRT-
SILÄ FINLAND OY [FI/IT]; Tarhaajantie 2, FI-65380
Vaasa (FI).


(72) Inventors; and

(75) Inventors/Applicants (for US only): LINTULA, Pekka

[FI/IT]: Vuoresojantie 71, FI-33850 Tampere (FI). TASK-
INEN, Kalevi [FI/IT]; Kattilaistentie 6, FI-33960 Pirkkala
(FI). LINTUNEN, Pertti [FI/IT]; Kaaponkuja 5 D 10,
FI-33820 Tampere (FI). SILVONEN, Aulis [FI/IT]; Hovi-
latie 28 as. 2, FI-65230 Vaasa (FI). LINDROOS, Tomi
[FI/IT]; Iisakinrinne 5, FI-37560 Lempäälä (FI).(74) Agent: AWEK INDUSTRIAL PATENTS LTD OY; P.O.
Box 230, FI-00101 Helsinki (FI).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

[Continued on next page]

(54) Title: SPARK PLUG AND METHOD FOR PRODUCING IT



(57) Abstract: A spark plug (1) for an internal combustion engine, the spark plug having at least two electrodes, in which the electrode (2.1, 2.2) are formed of a first part (5) made of a substrate material and a surface part (7) more durable than the substrate material. The surface part (7) of the spark plug is joined to the first part via an intermediate part (6) making use of explosion welding. The method also relates to a method for producing a spark plug (1) for an internal combustion engine, the spark plug having at least two electrodes (2.1, 2.2).

WO 2004/084367 A1